







|                      |   |   |   |  |   |   |   |   |   |   |
|----------------------|---|---|---|--|---|---|---|---|---|---|
| <b>Model</b>         |  |  |  |  |  |  |  |  |  |  |
| <b>Product Title</b> | SecurView Internet Camera   | SecurView Wireless Internet Camera  | SecurView Wireless Day/Night Internet Camera                                      | SecurView PoE Dome Internet Camera (Fixed Position)                                | SecurView Day/Night Internet Camera   | SecurView Wireless Day/Night Internet Camera  | SecurView Pan/Tilt/Zoom Internet Camera   | SecurView Wireless Pan/Tilt/Zoom Internet Camera                                    | SecurView Day/Night Pan/Tilt/Zoom Internet Camera                                   | SecurView Wireless Day/Night Pan/Tilt/Zoom Internet Camera                          |

## Features

|                          |                                       |  |  |  |  |  |  |
|--------------------------|---------------------------------------|--|--|--|--|--|--|
| <b>Software Included</b> | SecurView (16 cameras)                | SecurView (16 cameras)                         | SecurView (16 cameras)                                     | SecurView (16 cameras)                         | SecurView (16 cameras)                         | SecurView (16 cameras)                   | SecurView (16 cameras)                         |
| <b>Image Sensor</b>      | 1/4" Progressive scan CMOS, 0.5 lux   | 1/4" Progressive scan CMOS, 0 lux night vision | 1/4" Progressive scan CMOS, 0.1 low lux                    | 1/4" Progressive scan CMOS, 0 lux night vision | 1/4" Progressive scan CMOS, 0 lux night vision | 1/4" Progressive scan CMOS, 0.5 lux      | 1/4" Progressive scan CMOS, 0 lux night vision |
| <b>Lens</b>              | 4.6mm/F2.6 fixed iris, 60° view angle | 4.5mm/F2.8 fixed iris IR, 60° view angle       | 4.0mm/F2.0 fixed iris, 62° view angle                      | 4.6mm/F2.8 fixed iris IR, 60° view angle       | 4.0mm/F1.8 fixed iris, 64° view angle          | 4.0mm/F1.8 fixed iris IR, 64° view angle | 4.0mm/F1.8 fixed iris IR, 64° view angle       |
| <b>Compression</b>       | MJPEG                                 | MJPEG  | MPEG-4/MJPEG   | MPEG-4/MJPEG                                   | MJPEG  | MPEG-4/MJPEG                             | MJPEG  |
| <b>Resolution</b>        | 640 x 480 pixels                      | 640 x 480 pixels                               | 640 x 480 pixels   | 640 x 480 pixels                               | 640 x 480 pixels                               | 640 x 480 pixels                         | 640 x 480 pixels                               |
| <b>Frames Per Second</b> | VGA: 30, QVGA: 30                     | VGA: 30, QVGA: 30                              | VGA: 30, QVGA: 30  | VGA: 30, QVGA: 30                              | VGA: 30, QVGA: 30                              | VGA: 30, QVGA: 30                        | VGA: 30, QVGA: 30                              |
| <b>3GPP Support</b>      | -                                     | -  | ✓  | ✓  | -  | -  | ✓  |
| <b>Zoom</b>              | 3x Digital                            | 3x Digital                                     | 3x Digital   | 3x Digital                                     | 3x Digital                                     | 3x Digital                               | 3x Digital                                     |
| <b>Audio Support</b>     | -                                     | 1-way  | 2-way  | 2-way  | -  | -  | 2-way  |
| <b>Vision</b>            | Day / low light mode                  | Day / night mode                               | Day / low light mode                                       | Day / night mode                               | Day / low light mode                           | Day / night mode                         | Day / night mode                               |
| <b>Pan and Tilt</b>      | -                                     | -  | Fixed position camera: manually adjust 350° pan, 160° tilt | -  | 330° pan, 105° tilt                            | 330° pan, 105° tilt                      | 330° pan, 105° tilt                            |
| <b>I/O Port - Rear</b>   | -                                     | -  | Yes  | -  | Yes  | Yes                                      | Yes  |
| <b>Mounting Base</b>     | Hardware included                     | Hardware included                              | Hardware included  | Hardware included                              | Hardware included                              | Hardware included                        | Hardware included                              |
| <b>Warranty</b>          | 3-year limited                        | 3-year limited                                 | 3-year limited   | 3-year limited                                 | 3-year limited                                 | 3-year limited                           | 3-year limited                                 |

## Compatible Enclosures

|                       |   |   |   |   |   |   |   |   |   |
|-----------------------|---|---|---|---|---|---|---|---|---|
| <b>Heater and Fan</b> | -   | ✓   | -   | ✓   | - | -   | ✓   | ✓   | - |
| <b>Part Number</b>    |  |  |  |  | - |  |  |  | - |
|                       | TV-H100   | TV-H110   | TV-H100   | TV-H110   |   | TV-H100   | TV-H110   | TV-H400   |   |